

Freestyle 2

The Most Portable 3D Scanner for Fast, Photorealistic 3D Reality Capture

The FARO® Freestyle 2 is a superior handheld 3D scanner designed for investigators and reconstructionists who require quick and easy complete scene documentation. Delivering fast, photorealistic 3D reality capture with unparalleled real-time display results, Freestyle 2 offers total mobility to scan even the most confined spaces and difficult objects.



Features

Real-Time Visualization

- Display lets you view what you capture as you scan

Wide-Range of Scanning Distances

- Captured 3D Points starts at 0.4 m
- Can be set to a maximum of 10 m

Capture in Variety of Lighting Conditions

- Designed for normally illuminated interiors and outdoors, including in overcast conditions
- Even provides usable data in complete darkness

One-Hand Operation

- Lightweight with no bulky tablet or long cables

Guided Scanning

- Haptic feedback alerts operator when adjustments need to be made to the users scanning technique
- Proprietary tracking engine enables users to make natural movements while scanning

On-Site Compensation

- White-balancing, post-processing can be done at the scene
- No annual calibration required

Integrated Training

- Live display of data quality with integrated training videos, and tutorials

Benefits

Ultimate Flexibility

- Freestyle 2 is portable, without the need for bulky computers
- Self-contained unit gives the freedom to scan around objects or inside spaces

Save Time

- Scan scenes and objects without data voids in minutes
- Captures data easily and in more detail in less time

Photorealistic Results

- Get high-quality, colored, 3D data with up to 0.5 mm accuracy

Confidence in What you Capture

- See a display of data as you capture to ensure you are getting what you need

Easy-to-learn & Easy-to-Use

- Modern user interface, proprietary tracking algorithms, integrated video tutorials

Performance Specifications

Range	0.4 - 5 m (up to 10 m with limited data quality)
Identifiable feature	Up to 0.2 mm
3D point accuracy¹	≤0.5 mm
Long range accuracy²	0.5 mm at 1 m distance 5 mm at 5 m distance 15 mm at 10 m distance
Single image point density	Up to 45,000 points/m ² in 0.5 m distance Up to 10,500 points/m ² in 1 m distance
Acquisition Rate³	Up to 220,000 points/s, point cloud density increases with time
Typical Noise⁴	<ul style="list-style-type: none">• 0.3 mm @ 0.4 m distance• 0.75 mm @ 1 m distance• 10 mm @ 3 m distance• 35 mm @ 5 m distance• 100 mm @ 10 m distance
Lighting conditions⁵	Full daylight, 10,000-45,000 lux (reduced performance in direct sunlight)
Light source	Integrated LED flash
Scan volume	39.5 m ³ @ max range 5 m
Typical field of view (HxW)	<ul style="list-style-type: none">• 420 mm x 550 mm @ 0.5 m• 930 mm x 1170 mm @ 1 m• 1800 mm x 2160 mm @ 2 m• 2740 mm x 3160 mm @ 3 m• 3600 mm x 4160 mm @ 4 m• 4470 mm x 5150 mm @ 5 m
Exposure time	0.1 ms - 7 ms (autoexposure)
Texture color	24 bit
Dimensions	285 mm x 256 mm x 130 mm
Connectivity	HDMI, USB 3.0, WiFi
Weight	1.48 kg
IP rating	IP 52
Compensation	Onsite - with supplied compensation plate
Op temperature range	0 - 40° C
Op humidity range	Non-condensing
Eye Safety	Class 1 Laser
Wavelength	798-816 nm

¹ 1 sigma standard deviation measured on reference scales of lengths between 0.3 m and 1 m, in 1 m distance, for a lateral scanner movement of 1 m, using targets for distance measurement ² Typical error at measured distances ³ Point density depends on scanned surface and lighting conditions ⁴ RMS

⁵ Limited range and point density in sunlight

* Dust protection 5. Water protection 2: Protection against dripping water whilst device in standard idle position with sensor side facing downward.

Mobile PC Specifications

Microsoft Windows 10 pro, 64-Bit Intel® Core™ i7

256 GB hard disc with 16 GB RAM

HDMI; USB 3.0 ports; WiFi


DICARLO
SALES - SUPPLIES - REPAIRS - RENTALS

www.dicarlotech.com
410-749-0112

Local offices in over 25 countries around the world. Go to www.faro.com to learn more.

FARO Global Headquarters

250 Technology Park, Lake Mary, FL 32746, USA

US: 800 736 0234 MX: +52 81 4170 3542

BR: 11 3500 4600 / 0800 892 1192

info@faro.com

FARO Europe Regional Headquarters

Lingwiesenstr. 11/2

70825 Korntal-Münchingen, Germany

00 800 3276 7253

info.emea@faro.com

FARO Asia Regional Headquarters

No. 3 Changi South Street 2, #01-01 Xilin
Districentre Building B Singapore, 486548

+65 65111350

asia@faro.com