RL-200 Series



High Accuracy, High Value Slope Lasers





- 7 Arc Second Accuracy
- Wide Grade Range (up to 25% slope) without Slope Blocks
- Extra-long Battery Life (100 hours)
- Increased Range Up to 3,600 ft. (1100m)
- Graphical Display
- Full Function Remote (RL-200 2S Only)



SPECIFICATIONS Horizontal ±7 arc seconds Accuracy Repeatability 7 arc seconds **Working Area** 3,600 ft. (1100m) 300/600/900 rpm **Rotation Speed Dust/Water Protection IP66 Operating Time** Alkaline: 100 hours Ni-MH: 90 hours **Grade Range** RL-200 2S: ±10 / -5 to +25 (single/dual) RL-200 1S: -5 to +25 / N/A Size (H x W x L) 253 x 218 x 174mm For more specification information:

topconpositioning.com/rl200-series

Five Year Guarantee

The RL-200 Series lasers come with a Five Year Guarantee. Topcon is backing up this reliable, accurate laser with the



best factory warranty in the industry.

Topcon TotalCare

This online resource comes with real live people ready to help. Get expert training from Topcon University's large collection of online materials, and expert help directly from Topcon Technical Support.

Access software and firmware updates, current publications, and guidance from the experts at Topcon all right from your computer or mobile device.

Please visit the TotalCare website to learn more. topcontotalcare.com



7400 National Drive • Livermore • CA 94550 (925) 245-8300

Specifications subject to change without notice. ©2013 Topcon Corporation All rights reserved. P/N: 7010-2128 Rev. A.1 TF Printed in U.S.A. 12/13

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

PRIMARY FEATURES

RL-200 Series

Topcon's RL-200 Series sets new standards for simplicity and accuracy. Rugged, lightweight, and compact, it's twice the laser at an amazingly affordable price!

RL-200 Series

Topcon's RL-200 Series revolutionary encoding system provides the highest grade repeatability, 7 arc seconds, of any other laser! No one even comes close. Setup after setup, time after time, you're always right on grade!


Choose from two models, RL-200 1S single slope, or RL-200 2S dual slope. The RL-200 1S provides single slopes from -5% up to +25%. The RL-200 2S provides dual slopes up to +/-10% in the X axis, or up to an industry leading -5 to +25% in the Y axis.

Control the RL-200 2S - remotely!

When the RL-200 2S is operating, the RC-400 displays all operating information up to 1,000 ft. (300m) away. Change grade, select menu settings, check operational status, even verify battery life, all without touching the laser!

Verifiable operation? It couldn't be clearer...

Topcon's RL-200 features a large, high-contrast, graphical display that clearly shows all functions at a glance:



RL-200 Menu Display

- 1. Current grade
- 2. Masking: Electronic shutter up to 3 quadrants
- 3. Selectable rotation speed: 300/600/900 rpm
- 4. Selectable remote channel: up to 9 channels
- 5. Sensitivity selector
- 6. HI alert: indicates when laser has been disturbed
- 7. HI alert to sensor

KIT COMPONENTS					
Model		RL-200 1S		RL-200 2S	
Laser	RL-200 2S			Х	Х
	RL-200 1S	Χ	Х		
Detector	LS-80L w/ Holder 6	X	Х	Х	х
Battery	Rechargeable Battery Kit		Х		х
	Dry Battery Kit	Χ		Х	
Remote Control	RC-400				Х

Rechargeable BT Kit: BT-67Q, DB-75C, AD-11 Dry BT Kit: DB-75, Dry Battery D size

Your local Authorized Topcon dealer is:

