



Specifications	
Accuracy	H: $\pm 20$ arc seconds
Self-Leveling Range	Horizontal $\pm 5^\circ$
Working Area	400 m
Rotation Speed	600 rpm
Dust/Water Rating	IP66
Operating Time	Alkaline: 100 hours Ni-MH: 60 hours
Operating Temp.	$-20^\circ\text{C}$ to $50^\circ\text{C}$
Size (H x W x L)	205 x 211 x 172 mm

## Self-Leveling Construction Laser



- Long-range operation (400 m)
- Smart long-range receiver
- Tough IP66 construction rating
- $\pm 20$  Arc second horizontal accuracy
- $\pm 5$  Degrees self-leveling range
- Up to 100 hours battery life

### Kit Components

- RL-H5B laser
- LS-80L sensor
- Sensor holder
- Batteries
- Carry case

### Five year guarantee

The RL-H5B laser comes with a Five Year Guarantee. Topcon is backing up this reliable, accurate laser with the best factory warranty in the industry.

### Long-range high accuracy laser

With great distance and high-accuracy, the RL-H5 Series is simple to use for checking elevations.

### Easy to use

With electronic self-leveling, you press the power button and go right to work in seconds. If the RL-H5B gets disturbed on the job it relevels itself automatically. The self-leveling motors are accurate to  $\pm 20$  arc seconds.

### Long range operation

Need to shoot elevations up to 400 m from your laser? No problem – this instrument has the power and range to cover a 400 m diameter job site.

### Long battery life

The RL-H5B provides up to 100 hours of continuous usage with 4 (D) cell batteries.

### All weather dependability

With the IP66 rating, the RL-H5B is “job site tough” and can withstand dust, a sudden shower and even torrential rainfall.



For more information:  
[topconpositioning.com/RL-H5B](http://topconpositioning.com/RL-H5B)

Specifications subject to change without notice.  
©2018 Topcon Corporation All rights reserved.  
7010-2248 A 2/18

  
**DICARLO**  
SALES - SUPPLIES - REPAIRS - RENTALS  
[www.dicarlotech.com](http://www.dicarlotech.com)  
410-749-0112